

TECHNICAL INFORMATION

Updated on 09.01.2023

CERAMICGUARD

impregnation of substrates with increased absorbency

IGOSA Sp. z o. o.
NIP 6482806063,
KRS 0000924493,
ul. Bronislawa
Hagera 41
41-800 Zabrze
biuro@igosa.eu
www.igosa.eu

APPLICATION.

CERAMICGUARD is designed for impregnation and protection against dirt on surfaces with increased absorption capacity (unglazed ceramic, stone and made of cement mortars, e.g. grouts). Impregnation of this type of surface with the preparation results in increased water resistance, resistance to dirt from oils, fats, coffee, tea, etc. After drying, CERAMICGUARD creates a durable and colorless protective coating, gives a delicate shine and a fresh look, and the elements covered with it become easier to maintain. The product does not contain solvents, is efficient and easy to use. It can be used both inside and outside buildings.

HOW TO USE

- **Preparation of the substrate:** The substrate should be degreased and cleaned of dust, dirt, lime, oils, grease and other impurities that may weaken adhesion (the manufacturer recommends Desolver PRO, Desolver Klinkier PRO or Polisol PRO to remove dirt). The entire surface intended for application must be thoroughly dried.
- **Preparation of the agent:** CERAMICGUARD is sold ready for direct application. It must not be mixed with other agents or diluted.
- **Application and drying:** CERAMICGUARD should be applied evenly (without leaving puddles) using a brush, sponge or cloth. In the case of very absorbent substrates, after approx. 30 minutes of drying, apply the preparation again. The floor should be used no earlier than 24 hours after applying the emulsion. The joints should be impregnated after they have hardened, at least 2 weeks after they have been made.

TECHNICAL DATA.

Substrate and ambient temperature	From +5°C to +30°C
Density	1.00+/-0.05 kg/dm3
Wear	From 0.04 to 0.07 L per 1 m2 (depending on the absorbency of the substrate)

PACKAGING.

Plastic bottles and canisters with a capacity of 1 l, 5 l, 10 l, 20 l or other upon agreement with the customer.

STORAGE AND TRANSPORT.

The product should be transported and stored in tightly closed, original packaging at temperatures from +5 °C to +30 °C. Protect from moisture, frost and sunlight. Close tightly after opening. Shelf life 24 months from the production date placed on the packaging.

The above information and recommendations are provided by the Manufacturer based on conducted research, tests and experience. The Manufacturer does not guarantee the achievement of an optimal final effect in the event of use not in accordance with the recommendations or storage conditions beyond the Manufacturer's control. The information contained in this document is based on currently available data characterizing the product and the Manufacturer's knowledge. It should be treated only as an aid for safe use, transport and storage of the product. This does not release the user from liability for improper use of the above information.

SECURITY.

May cause an allergic skin reaction.

Keep out of reach of children.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of water.

If skin irritation or rash occurs: Get medical advice/ attention.

NOTE! Product intended for professional use. The manufacturer and distributor are not responsible for damage caused by improper use.

The above information and recommendations are provided by the Manufacturer based on conducted research, tests and experience. The Manufacturer does not guarantee the achievement of an optimal final effect in the event of use not in accordance with the recommendations or storage conditions beyond the Manufacturer's control. The information contained in this document is based on currently available data characterizing the product and the Manufacturer's knowledge. It should be treated only as an aid for safe use, transport and storage of the product. This does not release the user from liability for improper use of the above information.