

TECHNICAL INFORMATION

Updated on 09.01.2023

GUARD CLINKER OIL

protection and care of unglazed surfaces ceramic

IGOSA Sp. z o. o. NIP 6482806063, KRS 0000924493, ul. Bronislawa Hagera 41 41-800 Zabrze <u>biuro@igosa.eu</u> www.igosa.eu

APPLICATION.

GUARD CLINKER OIL is a solvent-free agent for the protection and maintenance of clinker, facing bricks, clay tiles and other unglazed ceramic surfaces. The preparation can be used to temporarily protect clinker surfaces from dirt during grouting. The use of Guard Clinker Oil deepens, revives and refreshes the colour, reduces sensitivity to dirt and stains and allows for easier maintenance.

HOW TO USE

• Preparation of the agent:

Guard Clinker Oil It is sold ready for direct application and should not be diluted.

• Preparation of the substrate:

Surfaces should be cleaned with soapy water. To remove salt efflorescence, dirt and mortar deposits or other dirt, the manufacturer recommends the Desolver Klinkier PRO cleaning agent, and in the case of greasy or polymer dirt (e.g. paints, primers), the manufacturer recommends Polisol PRO. After cleaning, leave the surface to dry. In order to obtain the best effect, it is recommended to perform a test on an inconspicuous part of the surface.

• Application and drying:

Apply the preparation with a brush, paint roller or cloth at an ambient temperature of +5°C to +30°C. NOTE: protect the joints from contact with Security Klinkier Oil. Remove excess agent with water and detergent.

Attention:

The preparation should not be used on non-absorbent surfaces. Not recommended for glazed, polished or varnished surfaces. Do not use leaching agents or agents with strong fat-dissolving properties for routine cleaning.

TECHNICAL DATA.

Wear	From 0.01 to 0.06 L per 1 m2 (depending on the absorbency of the substrate)
Density	0.87+/- 0.01 kg/dm3 (15°C)
Ambient, preparation and substrate temperature	From +5°C to +30°C

PACKAGING.

Plastic bottles and canisters with a capacity of 1 l, 5 l, 10 l, 20 l or other upon agreement with the customer.

STORAGE AND TRANSPORT.

The product should be transported and stored in tightly closed, original packaging at temperatures from $+5 \degree C$ to $+30 \degree C$. Protect from moisture, frost and sunlight. Close tightly after opening. Shelf life 36 months from the production date placed on the packaging.

The above information and recommendations are provided by the Manufacturer based on conducted research, tests and experience. The Manufacturer does not guarantee the achievement of an optimal final effect in the event of use not in accordance with the recommendations or storage conditions beyond the Manufacturer's control. The information contained in this document is based on currently available data characterizing the product and the Manufacturer's knowledge. It should be treated only as an aid for safe use, transport and storage of the product. This does not release the user from liability for improper use of the above information.

SECURITY.

Keep out of reach of children.

ATTENTION! Product intended for professional use. The manufacturer and distributor are not responsible for damage caused by improper use.

The above information and recommendations are provided by the Manufacturer based on conducted research, tests and experience. The Manufacturer does not guarantee the achievement of an optimal final effect in the event of use not in accordance with the recommendations or storage conditions beyond the Manufacturer's control. The information contained in this document is based on currently available data characterizing the product and the Manufacturer's knowledge. It should be treated only as an aid for safe use, transport and storage of the product. This does not release the user from liability for improper use of the above information.