

TECHNICAL INFORMATION

Updated on 09.01.2023

Polisol PRO

a product for removing residues of polymer adhesives

IGOSA Sp. z o. o.
NIP 6482806063,
KRS 0000924493,
ul. Bronislawa
Hagera 41
41-800 Zabrze
biuro@igosa.eu
www.igosa.eu

APPLICATION.

Polysol PRO is an efficient and very effective preparation designed to remove residues, dirt and deposits from various types of polymer adhesives, primers and emulsion paints. It is also suitable for washing dirt, deposits and stains resulting from oils and greases. Thanks to its optimally selected formula, it allows for quick removal of even the oldest dirt. It is used to clean ceramic, stone, clinker tiles, chrome, varnished, glass, stainless steel and plastic surfaces. Polisol PRO can be used inside and outside the building.

HOW TO USE

It is best to use a brush or a sharp sponge to apply the product to the dirt and then clean the surface. Depending on the intensity and type of dirt, the product can be used undiluted or after dilution with water in a maximum ratio of 1 part of the product to 5 parts of water. Particularly heavily soiled areas should be soaked with the product without dilution and left for approx. 15 minutes so that the agent penetrates deeply. Then you can start removing the dirt. In each case, the surface cleaned of dirt should be thoroughly rinsed with clean water.

Before applying the agent, it is recommended to perform a cleaning test. The preparation may cause discoloration of plastic surfaces. Clean tools with clean water immediately after use.

TECHNICAL DATA.

Substrate and ambient temperature	From +5°C to +30°C
Density	1.02+/-0.02 kg/dm3
Reaction	Alkaline

PACKAGING.

Plastic bottles and canisters with a capacity of 1 l, 5 l, 10 l, 20 l or other upon agreement with the customer.

STORAGE AND TRANSPORT.

The product should be transported and stored in tightly closed, original packaging at temperatures from +5 °C to +25 °C. Protect from moisture, frost and sunlight. Close tightly after opening. Shelf life 24 months from the production date placed on the packaging.

SECURITY.

NOTE: alkaline agent.

Eye irritation category 2 (Eye Irrit. 2).

Irritating to eyes.

Repeated exposure may cause skin dryness or cracking.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of soap and water.

The above information and recommendations are provided by the Manufacturer based on conducted research, tests and experience. The Manufacturer does not guarantee the achievement of an optimal final effect in the event of use not in accordance with the recommendations or storage conditions beyond the Manufacturer's control. The information contained in this document is based on currently available data characterizing the product and the Manufacturer's knowledge. It should be treated only as an aid for safe use, transport and storage of the product. This does not release the user from liability for improper use of the above information.

